

SAFETY DATA SHEET
WOOD KOTE PRODUCTS INC.
www.woodkote.com

Section 1: Product and Company Identification

Product Name: LaqAdd Product Code: 606

WOOD KOTE PRODUCTS INC.
8000 NE 14th Place
Portland, Oregon 97211
USA

TEL: 503-285-8371
800-843-7666 (Toll Free USA & Canada)
FAX: 503-285-8374
E-MAIL: info@woodkote.com

EMERGENCY CONTACT
INFOTRAC (Transportation): 800-535-5053

Product Use: Lacquer Retarder. This product is intended for professional use and application only.

Section 2: Hazards Identification

GHS Ratings:

Flammable liquid	4	Flash point $\geq 60^{\circ}\text{C}$ (140°F) and $\leq 93^{\circ}\text{C}$ (200°F)
Oral Toxicity	Acute Tox. 4	Oral >300 and ≤ 2000 mg/kg
Dermal Toxicity	Acute Tox. 4	Dermal >1000 and ≤ 2000 mg/kg
Inhalation Toxicity	Acute Tox. 4	Gases >2500 and ≤ 5000 ppm, Vapors >10 and ≤ 20 mg/l, Dusts & mists >1 and ≤ 5 mg/l.
Skin corrosive	2	Reversible adverse effects in dermal tissue. Draize score: ≥ 2.3 < 4.0 or persistent inflammation.
Eye corrosive	2A	Eye irritant: subcategory 2A, reversible in 21 days.

GHS Hazards

H227	Combustible liquid.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

GHS Precautions

P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists, get medical advice/attention.
P370+P378	In case of fire: Use water fog, "alcohol" foam, dry chemical, or CO ₂ .
P403+P235	Store in a well ventilated place. Keep cool.
P501WK	If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

Signal Word: Warning



Section 3: Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Ethylene Glycol Butyl Ether	111-76-2	100.00%

Section 4: First Aid Measures

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.

IF ON SKIN: Gently wash with plenty of soap and water.

IF SWALLOWED: DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

Note to Physician: Provide general supportive measures and treat symptomatically.

Section 5: Fire Fighting Measures

Flash Point: 66 C (151 F)

LEL: 1.00

UEL: 13.00

EXTINGUISHING MEDIA: Alcohol resistant foam. Water fog. Dry chemical powder. Carbon Dioxide (CO₂).

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and gear when fighting fires involving this material. Although not flammable as supplied, this material is a strong oxidizer and will contribute copious amounts of oxygen during decomposition.

FIRE EQUIPMENT: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NOISH approved, self-contained breathing apparatus.

Section 6: Accidental Release Measures

PERSONAL PRECAUTIONS: Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers unless wearing appropriate protective clothing.

EMERGENCY PROCEDURES: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering.

SMALL SPILLS: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.

LARGE SPILLS: Dike far ahead of liquid spill for later disposal. Keep material out of storm sewers and ditches which lead to waterways.

Section 7: Handling and Storage

HANDLING: Do not taste or swallow. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

STORAGE: Keep in original container tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

COMMENTS: Read label before use. KEEP OUT OF REACH OF CHILDREN! Empty containers, retain product residue (liquid and/or vapor).

Section 8: Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Ethylene Glycol Butyl Ether 111-76-2	TWA 50 ppm 240 mg/m ³	TWA 20 ppm	NIOSH: TWA 5 ppm 24 mg/m ³

ENGINEERING CONTROLS: Provide general local exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

VENTILATION: Good general ventilation should be used. Ventilation rates should be matched to conditions

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety goggles. Maintain eye wash fountain and quick drench facilities in work areas.

SKIN: Wear protective gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

WORK HYGIENIC PRACTICES: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

OTHER USE PRECAUTIONS: May be harmful if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

CONTAMINATED GEAR: Take off contaminated clothing and wash it before reuse. Follow manufacturer's instructions for cleaning. If no such instructions for washables, use detergent and hot water.

Section 9: Physical and Chemical Properties

Appearance: Translucent Viscosity: 3.3 mPa.s (20 °C) PH Essentially neutral. Decomposition temperature: N/A Vapor Density: 4.08 - (Air=1.0) Freezing point: N/A Flash point: 151 F,66 C Evaporation rate: Slower than butyl acetate. Percent Volatile: 100	Odor: Sweet, Ester-Like Solubility: Ketones, Hydrocarbons, and Water Autoignition temperature: 230°C Vapor Pressure: 13 hPa (10 mmHg) at 81°C Melting point: N/A Boiling range: 169°C Specific Gravity (SG) 0.901
---	--

Section 10: Stability and Reactivity

Stability:

Under normal conditions:

STABLE

Incompatibilities:

Strong oxidizers.

Chemical stability: Stable under recommended storage conditions.

Avoid heat, sparks, open flames and other ignition sources.

Hazardous decomposition:

Hazardous decomposition products formed under fire conditions - Carbon oxides.

Hazardous polymerization will not occur.

Section 11: Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 880mg/kg

Dermal Toxicity LD50: 1,060mg/kg

Component Toxicity

111-76-2

Ethylene Glycol Butyl Ether

Oral LD50: 880 mg/kg (Rat) Dermal LD50: 1,060 mg/kg (Rabbit)

Section 12: Ecological Information

ENVIRONMENTAL SUMMARY: Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

Section 13: Disposal Considerations

DISPOSAL: If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

Section 14: Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
	NDA			

Section 15: Regulatory Information

ACGIH (American Conference of Governmental Industrial Hygienists)

TWA (Time-Weighted Average)

OSHA (Occupational Safety and Health Administration)

NIOSH (National Institute for Occupational Safety and Health)

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product does not contain chemicals that are listed by the State of California as carcinogenic or a reproductive toxin.

OSHA: Occupational Safety and Health Administration.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

SARA TITLE III (Superfund Amendment and Reauthorization Act)

SARA 302 Components:

No chemicals in this product are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards:

111-76-2 Ethylene Glycol Butyl Ether 100 % Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA 313 Components:

111-76-2 Ethylene Glycol Butyl Ether 100 %

Section 16: Other Information


ABBREVIATIONS USED IN THE SDS:

NDA: No Data Available

Hazardous Material Information System (HMIS)

HEALTH	2	HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH
FLAMMABILITY	2	
PHYSICAL HAZARD	0	
PERSONAL PROTECTION	G	

National Fire Protection Association (NFPA)



DISCLAIMER: The information contained herein is based on data available to us and is believed to be correct. WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 10/24/2016