

SAFETY DATA SHEET
WOOD KOTE PRODUCTS INC.
www.woodkote.com

Section 1: Product and Company Identification

Product Name: Korrekt-O White Product Code: 0K0061

WOOD KOTE PRODUCTS INC.
8000 NE 14th Place
Portland, Oregon 97211
USA

TEL: 503-285-8371
800-843-7666 (Toll Free USA & Canada)
FAX: 503-285-8374
E-MAIL: info@woodkote.com

EMERGENCY CONTACT
INFOTRAC (Transportation): 800-535-5053

Product Use: Industrial Colorants. This product is intended for professional use and application only.

Section 2: Hazards Identification

GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Reproductive toxin	1B	Presumed, based on experimental animals.
Organ toxin repeated exposure	1	Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies. Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidance) - Human evidence in exceptional cases.

GHS Hazards

H226	Flammable liquid and vapour.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

GHS Precautions

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P370+P378	In case of fire: Use water fog, "alcohol" foam, dry chemical, or CO2.

P405
P403+P235
P501WK

Store locked up.
Store in a well ventilated place. Keep cool
If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

Signal Word: Danger



FLAMMABLE LIQUID AND VAPOR

Section 3: Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
2-Methoxy-1-Methylethyl Acetate	108-65-6	10.00% - 20.00%
Aluminum Hydroxide	21645-51-2	5.00% - 10.00%
Silica	112945-52-5	1.00% - 5.00%
Solvent Naphtha (petroleum), Medium Aliphatic	64742-88-7	1.00% - 5.00%

Section 4: First Aid Measures

IF INHALED: Move to fresh air. Call a physician if symptoms develop or persist.

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persist.

IF SWALLOWED: Rinse mouth. Get medical attention if symptoms occur.

Note to Physician: Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Section 5: Fire Fighting Measures

Flash Point: 42 C (108 F)

LEL: 1.00

UEL: 13.00

EXTINGUISHING MEDIA: Alcohol resistant foam. Water fog. Dry chemical powder. Carbon Dioxide (CO₂).

EXPLOSION HAZARDS: Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

FIRE FIGHTING PROCEDURES: In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and gear when fighting fires involving this material.

Section 6: Accidental Release Measures

PERSONAL PRECAUTIONS: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

SMALL SPILLS: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.

LARGE SPILLS: Stop the flow of the material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Section 7: Handling and Storage

HANDLING: Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact during pregnancy/while nursing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE: Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials. Keep in an area equipped with sprinklers.

COMMENTS: Read label before use. KEEP OUT OF REACH OF CHILDREN! Empty containers, retain product residue (liquid and/or vapor). Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

Section 8: Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
2-Methoxy-1-Methylethyl Acetate 108-65-6	NDA	NDA	WEEL: TWA 50 ppm
Aluminum Hydroxide 21645-51-2	NDA	NDA	NDA
Silica 112945-52-5	TWA 20 Million particles per cubic foot.	NDA	NIOSH: TWA 6 mg/m ³
Solvent Naphtha (petroleum), Medium Aliphatic 64742-88-7	PEL 500 ppm 2,900 mg/m ³ TWA 100 ppm 525 mg/m ³	TWA 100 ppm	NDA

ENGINEERING CONTROLS: Provide general local exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety goggles. Maintain eye wash fountain and quick drench facilities in work areas.

SKIN: Wear protective gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

WORK HYGIENIC PRACTICES: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

OTHER USE PRECAUTIONS: May be harmful if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

CONTAMINATED GEAR: Take off contaminated clothing and wash it before reuse. Follow manufacturer's instructions for cleaning. If no such instructions for washables, use detergent and hot water.

Section 9: Physical and Chemical Properties

<p>Appearance: Paste / White</p> <p>Solubility in Water: Negligible.</p> <p>Flash point: 42 C</p> <p>Evaporation Rate: Slower than butyl acetate</p> <p>VOC g/L (Coating) 387</p>	<p>Odor: Sweet Ether-like.</p> <p>Boiling point: 145°C</p> <p>Specific Gravity (SG) 1.899</p> <p>Viscosity: 85 - 105 KU (25 °C)</p>
--	---

Section 10: Stability and Reactivity

Stability:

Under normal conditions:

STABLE

Incompatibilities:

Avoid heat, sparks, open flames and other ignition sources.

Strong oxidizers.

Hazardous decomposition:

Carbon monoxide and carbon dioxide.

Oxygen, hydrogen gas, water, heat, steam.

Hazardous polymerization will not occur.

Section 11: Toxicological Information

Component Toxicity

108-65-6	2-Methoxy-1-Methylethyl Acetate Dermal LD50: 2,000 mg/kg (Rat)
21645-51-2	Aluminum Hydroxide Oral LD50: 2,000 mg/kg (Rat)
64742-88-7	Solvent Naphtha (petroleum), Medium Aliphatic Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 3,000 mg/kg (Rabbit)

PRIMARY ROUTES OF ENTRY

Inhalation

Target Organs: Lungs

Section 12: Ecological Information

ENVIRONMENTAL SUMMARY: Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

Component Ecotoxicity

2-Methoxy-1-Methylethyl Acetate

Toxicity to fish: Mortality LC50 - *Salmo gairdneri* - 100-180 mg/l - 96 hr (OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates: Static test EC50 - *Daphnia magna* (Water flea) ->500 mg/l - 48hr

Solvent Naphtha (petroleum),
Medium Aliphatic

Very toxic for fish.

Section 13: Disposal Considerations

DISPOSAL: If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

Section 14: Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Paint	1263	III	3
IATA	Paint	1263	III	3
IMDG/IMO	Paint	1263	III	3

Section 15: Regulatory Information

ACGIH (American Conference of Governmental Industrial Hygienists)

TWA (Time-Weighted Average)

OSHA (Occupational Safety and Health Administration)

NIOSH (National Institute for Occupational Safety and Health)

TSCA: All components are on the U.S. EPA TSCA Inventory List.

OSHA: Occupational Safety and Health Administration.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA TITLE III (Superfund Amendment and Reauthorization Act)

SARA 302 Components:

No chemicals in this product are subject to the reporting requirements of SARA Title III, Section 302

SARA 311/312 Hazards:

64742-88-7 Solvent Naphtha (petroleum), Medium Aliphatic 1 to 5 % Fire Hazard, Acute Health Hazard, Delayed Hazard

SARA 313 Components:

No chemicals in this product are subject to the reporting requirements of SARA Title III, Section 313.

Section 16: Other Information

ABBREVIATIONS USED IN THE SDS:


NDA: No Data Available

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	H

HMIS & NFPA Hazard Rating Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



DISCLAIMER: The information contained herein is based on data available to us and is believed to be correct. WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 2/23/2016