

SAFETY DATA SHEET
WOOD KOTE PRODUCTS INC.
www.woodkote.com

Section 1: Product and Company Identification

Product Name: BrushLaq 680 - Satin Product Code: 115

WOOD KOTE PRODUCTS INC.
8000 NE 14th Place
Portland, Oregon 97211
USA

TEL: 503-285-8371
800-843-7666 (Toll Free USA & Canada)
FAX: 503-285-8374
E-MAIL: info@woodkote.com

EMERGENCY CONTACT
INFOTRAC (Transportation): 800-535-5053

Product Use: Brushing Lacquer. This product is intended for professional use and application only.

Section 2: Hazards Identification

GHS Ratings:

| | | |
|---------------------|--------------|--|
| Flammable liquid | 2 | Flash point < 23°C and initial boiling point > 35°C (95°F) |
| Oral Toxicity | Acute Tox. 3 | Oral>50+<=300mg/kg |
| Dermal Toxicity | Acute Tox. 3 | Dermal>200+<=1000mg/kg |
| Inhalation Toxicity | Acute Tox. 3 | Gases>500+<=2500ppm, Vapors>2+<=10mg/l, Dusts&mists>0.5+<=1mg/l. |
| Skin corrosive | 3 | Reversible adverse effects in dermal tissue. Draize score: >= 1.5 < 2.3. |
| Eye corrosive | 2A | Eye irritant: subcategory 2A, reversible in 21 days. |
| Carcinogen | 2 | Limited evidence of human or animal carcinogenicity. |
| Reproductive toxin | 1B | Presumed, based on experimental animals. |
| Aspiration hazard | 1 | Aspiration Toxicity Category 1: known (regarded)- human evidence - hydrocarbons with kinematic viscosity 20.5 mm ² /s at 40° C. |

GHS Hazards

| | |
|------|---|
| H225 | Highly flammable liquid and vapour. |
| H301 | Toxic if swallowed. |
| H311 | Toxic in contact with skin. |
| H316 | Causes mild skin irritation. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H351 | Suspected of causing cancer. |
| H360 | May damage fertility or the unborn child. |

GHS Precautions

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces - No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/light/equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe mist/vapours/spray. |
| P264 | Wash skin thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P285 | In case of inadequate ventilation wear respiratory protection. |

| | |
|----------------|--|
| P331 | Do NOT induce vomiting. |
| P363 | Wash contaminated clothing before reuse. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing . Rinse skin with water/shower. |
| P304+P312 | IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. |
| P305+P351+P338 | IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P337+P313 | If eye irritation persists, get medical advice/attention. |
| P370+P378 | In case of fire: Use water fog, "alcohol" foam, dry chemical, or CO2. |
| P405 | Store locked up. |
| P403+P235 | Store in a well ventilated place. Keep cool. |
| P501WK | If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment. |

Signal Word: Danger



**HIGHLY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE.**

Section 3: Composition / Information on Ingredients

| Chemical Name | CAS number | Weight Concentration % |
|---|-------------|------------------------|
| Polymer/Solids | Proprietary | 28.00% |
| Solvent Naphtha (petroleum), Medium Aliphatic | 64742-88-7 | 13.00% |
| Ethylene Glycol Butyl Ether | 111-76-2 | 10.00% |
| Isobutyl Acetate | 110-19-0 | 10.00% |
| Isobutyl Isobutyrate | 97-85-8 | 9.00% |
| Methyl Amyl Ketone | 110-43-0 | 9.00% |
| Isopropyl Alcohol | 67-63-0 | 6.00% |
| Solvent Naphtha, Light Aliiphatic | 64742-89-8 | 5.00% |
| Nitrocellulose | 9004-70-0 | 5.00% |
| Rosin, Maleated, Polymer with Glycerol | 68038-41-5 | 2.00% |
| Butyl Benzyl Phthalate | 85-68-7 | 1.00% |
| Xylene (o-,m-,p- isomers) | 1330-20-7 | 0.50% |

Section 4: First Aid Measures

IF INHALED: If breathing is difficult, remove source of exposure or move victim to fresh air and keep at rest in a position comfortable for breathing. If victim is not breathing, call 911 and administer CPR as directed.

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.

IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persist.

IF SWALLOWED: DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs . Get medical attention.

Note to Physician: Provide general supportive measures and treat symptomatically.

Section 5: Fire Fighting Measures

Flash Point: 10 C (50 F)

LEL: 1.00

UEL: 13.00

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical, or CO₂.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flashpoint.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

FIRE FIGHTING PROCEDURES: DANGER! Highly flammable liquid and vapor. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Clear fire area of unprotected personnel. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. Use water spray to cool containers exposed to fire.

FIRE EQUIPMENT: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NOISH approved, self-contained breathing apparatus.

Section 6: Accidental Release Measures

PERSONAL PRECAUTIONS: Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers unless wearing appropriate protective clothing.

EMERGENCY PROCEDURES: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering.

CONTAINMENT/CLEAN-UP MEASURES: Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

LARGE SPILLS: Stop the flow of the material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Section 7: Handling and Storage

HANDLING: Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact during pregnancy/while nursing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Store in flammables area. Keep in original container tightly closed when not in use.

COMMENTS: Read label before use. KEEP OUT OF REACH OF CHILDREN! Empty containers, retain product residue (liquid and/or vapor). Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

Section 8: Exposure Control and Personal Protection

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|---|--|-------------------------------|----------------------------------|
| Polymer/Solids Proprietary | NDA | NDA | NDA |
| Solvent Naphtha (petroleum) Medium Aliphatic 64742-88-7 | PEL 500 ppm 2,900 mg/m3 TWA 100 ppm 525 mg/m3 | TWA 100 ppm | NDA |
| Ethylene Glycol Butyl Ether 111-76-2 | TWA 50 ppm 240 mg/m3 | TWA 20 ppm | NIOSH: TWA 5 ppm 24 mg/m3 |
| Isobutyl Acetate 110-19-0 | TWA 150 ppm 700 mg/m3 | TWA 150 ppm | NIOSH: TWA 150 ppm 700 mg/m3 |
| Isobutyl Isobutyrate 97-85-8 | NDA | NDA | NDA |
| Methyl Amyl Ketone 110-43-0 | TWA 100 ppm - 465 mg/m3 | TWA 50 ppm - 233 mg/m3 | NDA |
| Isopropyl Alcohol 67-63-0 | TWA 400 ppm 980 mg/m3 | TWA 200 ppm STEL 400 ppm | NIOSH: TWA 400 ppm 980 mg/m3 |
| Solvent Naphtha, Light Aliphatic 64742-89-8 | TWA 500 ppm | TWA 300 ppm 1,370 mg/m3 | NDA |
| Nitrocellulose 9004-70-0 | TWA 400 ppm 1,200 mg/m3 | TWA 400 ppm STEL 500 ppm | NIOSH: TWA 1,000 ppm 1,900 mg/m3 |
| Rosin, Maleated, Polymer with Glycerol 68038-41-5 | NDA | NDA | NDA |
| Butyl Benzyl Phthalate 85-68-7 | NDA | NDA | NDA |
| Xylene (o-,m-,p- isomers) 1330-20-7 | TWA 100 ppm 435 mg/m3 | STEL: 150 ppm TWA: 100 ppm | TWA 100 ppm 435 mg/m3 |

ENGINEERING CONTROLS: Provide general local exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

VENTILATION: General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety goggles. Maintain eye wash fountain and quick drench facilities in work areas.

SKIN: Wear protective gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

WORK HYGIENIC PRACTICES: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

OTHER USE PRECAUTIONS: Toxic if swallowed and enters airways. May irritate body tissues. Use with adequate ventilation. Do not breath vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

CONTAMINATED GEAR: Take off contaminated clothing and wash it before reuse. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

Section 9: Physical and Chemical Properties

| | |
|--|--|
| <p>Appearance: Translucent</p> <p>Viscosity: N/A</p> <p>PH Essentially neutral.</p> <p>Decomposition temperature: N/A</p> <p>Vapor Density: 3.9</p> <p>Freezing point: N/A</p> <p>Flash point: 50 F, 10 C</p> <p>Specific Gravity (SG) 0.922</p> <p>VOC g/L (Coating) 512.9</p> | <p>Odor: Typical lacquer solvent.</p> <p>Solubility: Ketones and hydrocarbons.</p> <p>Autoignition temperature: 170°C</p> <p>Vapor Pressure: 205.7 at 37.70 C</p> <p>Melting point: N/A</p> <p>Boiling range: 35°C</p> <p>Evaporation rate: Slower than butyl acetate.</p> <p>VOC g/L (Material) 512.9</p> |
|--|--|

Section 10: Stability and Reactivity

Stability:

Under normal conditions:

STABLE

Incompatibilities:

No decomposition if used and stored according to specifications.

Strong oxidizers.

Avoid heat, sparks, open flames and other ignition sources.

Hazardous decomposition:

Carbon monoxide and carbon dioxide.

Oxygen, hydrogen gas, water, heat, steam.

Hazardous polymerization will not occur.

Section 11: Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 2,436mg/kg

Dermal Toxicity LD50: 127mg/kg

Component Toxicity

| | |
|------------|---|
| 64742-88-7 | Solvent Naphtha (petroleum), Medium Aliphatic Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 3,000 mg/kg (Rabbit) |
| 111-76-2 | Ethylene Glycol Butyl Ether Oral LD50: 470 mg/kg (Rat) |
| 110-43-0 | Methyl Amyl Ketone Oral LD50: 730 mg/kg (Mouse) Dermal LD50: 13 mL/kg (Guinea Pig) Inhalation LC50: 2,000 pp |
| 67-63-0 | Isopropyl Alcohol Oral LD50: 3,600 mg/kg (Mouse) |
| 64742-89-8 | Solvent Naphtha, Light Aliiphatic Dermal LD50: 4,000 mg/kg (Rat) Inhalation LC50: 3,400 ppm (Rat) |
| 9004-70-0 | Nitrocellulose Oral LD50: 5 g/kg (rat) |
| 85-68-7 | Butyl Benzyl Phthalate Oral LD50: 2,330 mg/kg (Rat) |

PRIMARY ROUTES OF ENTRY

Inhalation

Target Organs: Kidneys, Liver, Lungs, Central Nervous System, Skin

Section 12: Ecological Information

ENVIRONMENTAL SUMMARY: Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

Component Ecotoxicity

| | |
|--|--|
| Solvent Naphtha (petroleum), Medium Aliphatic | Very toxic for fish. |
| Methyl Amyl Ketone | Toxicity to fish: LC50 - Pimephales promelas (fathead minnow): 126-137 mg/l, 96 hr. Toxicity to daphnia and other aquatic invertebrates: semi-static test EC50- Daphnia magna (water flea): >90.1mg/l, 72 hr. Toxicity to algae: static test EC50 - Pseudokirchneriella subcapitata (algae): 98.2 mg/l, 72 hr. |
| Isopropyl Alcohol | (LC50): 100000 mg/l 96 hours [Fathead Minnow]. 64000 mg/l 96 hours [Fathead Minnow]. |

Section 13: Disposal Considerations

DISPOSAL: If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment`

Section 14: Transport Information

| <u>Agency</u> | <u>Proper Shipping Name</u> | <u>UN Number</u> | <u>Packing Group</u> | <u>Hazard Class</u> |
|---------------|-----------------------------|------------------|----------------------|---------------------|
| DOT | Paint | 1263 | III | 2 |
| IATA | Paint | 1263 | III | 2 |
| IMDG/IMO | Paint | 1263 | III | 2 |

Section 15: Regulatory Information

- ACGIH** (American Conference of Governmental Industrial Hygienists)
- TWA** (Time-Weighted Average)
- OSHA** (Occupational Safety and Health Administration)
- NIOSH** (National Institute for Occupational Safety and Health)

Section 16: Other Information

ABBREVIATIONS USED IN THE SDS:


NDA: No Data Available

Hazardous Material Information System (HMIS)

| | |
|---------------------|---|
| HEALTH | 2 |
| FLAMMABILITY | 2 |
| PHYSICAL HAZARD | 0 |
| PERSONAL PROTECTION | H |

HMIS & NFPA Hazard Rating Legend
 * = Chronic Health Hazard
 0 = INSIGNIFICANT
 1 = SLIGHT
 2 = MODERATE
 3 = HIGH

National Fire Protection Association (NFPA)



DISCLAIMER: The information contained herein is based on data available to us and is believed to be correct. WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 8/2/2016