

SAFETY DATA SHEET
WOOD KOTE PRODUCTS INC.
www.woodkote.com

Section 1: Product and Company Identification

Product Name: PolySolvent Product Code: 4500

WOOD KOTE PRODUCTS INC.

8000 NE 14th Place
Portland, Oregon 97211
USA

TEL: 503-285-8371
800-843-7666 (Toll Free USA & Canada)
FAX: 503-285-8374
E-MAIL: info@woodkote.com

EMERGENCY CONTACT

INFOTRAC (Transportation): 800-535-5053

Product Use: Mineral Spirits. This product is intended for professional use and application only.

Section 2: Hazards Identification

GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Aspiration hazard	2	Aspiration Toxicity Category 2: Presumed- Based on animal studies- surface tension, water solubility, boiling point- kinematic viscosity 14 mm ² /s at 40°C & not Category 1.

GHS Hazards

H226	Flammable liquid and vapour.
H305	May be harmful if swallowed and enters airways.

GHS Precautions

P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P331	Do NOT induce vomiting.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P370+P378	In case of fire: Use water fog, "alcohol" foam, dry chemical, or CO ₂ .
P405	Store locked up.
P403+P233	Store in a well ventilated place. Keep container tightly closed
P501	Disposal: If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

Signal Word: Warning



Section 3: Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Solvent Naphtha (petroleum), Medium Aliphatic	64742-88-7	100.00%

Section 4: First Aid Measures

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persist.

IF SWALLOWED: DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

Note to Physician: Provide general supportive measures and treat symptomatically.

Section 5: Fire Fighting Measures

Flash Point: 43 C (109 F)

LEL: 1.00

UEL: 7.00

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical, or CO₂.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

FIRE FIGHTING PROCEDURES: WARNING! Flammable liquid and vapor. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Clear fire area of unprotected personnel. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. Use water spray to cool containers exposed to fire.

FIRE EQUIPMENT: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NOISH approved, self-contained breathing apparatus.

Section 6: Accidental Release Measures

PERSONAL PRECAUTIONS: Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers unless wearing appropriate protective clothing.

EMERGENCY PROCEDURES: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering.

CONTAINMENT/CLEAN-UP MEASURES: Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

LARGE SPILLS: Dike far ahead of liquid spill for later disposal. Keep material out of storm sewers and ditches which lead to waterways.

Section 7: Handling and Storage

HANDLING: Do not taste or swallow. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

STORAGE: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Store in flammables area. Keep in original container tightly closed when not in use.

COMMENTS: Read label before use. KEEP OUT OF REACH OF CHILDREN! Empty containers, retain product residue (liquid and/or vapor). Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

Section 8: Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Solvent Naphtha (petroleum) Medium Aliphatic 64742-88-7	PEL 500 ppm 2,900 mg/m ³ TWA 100 ppm 525 mg/m ³	TWA 100 ppm	NDA

ENGINEERING CONTROLS: Provide general local exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

VENTILATION: Good general ventilation should be used. Ventilation rates should be matched to conditions

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety goggles. Maintain eye wash fountain and quick drench facilities in work areas.

SKIN: Wear protective gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

WORK HYGIENIC PRACTICES: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

OTHER USE PRECAUTIONS: May be harmful if swallowed and enter airways. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

CONTAMINATED GEAR: Take off contaminated clothing and wash it before reuse. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

Section 9: Physical and Chemical Properties

Appearance: Translucent Viscosity: 1.5centistokes (25°C / 77°F) PH 5.5-6 Decomposition temperature: N/A Vapor Density: (air = 1) 4.0 Freezing point: -70°C (-94°F) Flash point: 109 F,43 C Specific Gravity (SG) 0.788	Odor: Stoddard/Mild Solubility: Ketones and Hydrocarbons Autoignition temperature: 230°C Vapor Pressure: (kPa at 20°C) 0.2-0.6 Melting point: N/A Boiling range: 160°C Evaporation rate: 0.1 (Butyl Acetate=1) Percent Volatile: 100
---	---

Section 10: Stability and Reactivity

Stability:

Under normal conditions:

STABLE

Incompatibilities:

Strong oxidizers.

Avoid heat, sparks, open flames and other ignition sources.

Hazardous decomposition:

Carbon monoxide and carbon dioxide.

Oxygen, hydrogen gas, water, heat, steam.

Hazardous polymerization will not occur.

Section 11: Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 5,000mg/kg

Dermal Toxicity LD50: 3,000mg/kg

Component Toxicity

64742-88-7

Solvent Naphtha (petroleum), Medium Aliphatic

Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 3,000 mg/kg (Rabbit)

PRIMARY ROUTES OF ENTRY

Inhalation

Target Organs: Lungs

Section 12: Ecological Information

ENVIRONMENTAL SUMMARY: Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

Component Ecotoxicity

Solvent Naphtha (petroleum),

Very toxic for fish.

Medium Aliphatic

Section 13: Disposal Considerations

DISPOSAL: If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

Section 14: Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Petroleum distillates, n.o.s	1268	III	3
IATA	Petroleum distillates, n.o.s	1268	III	3
IMDG/IMO	Petroleum distillates, n.o.s	1268	III	3

Section 15: Regulatory Information

ACGIH (American Conference of Governmental Industrial Hygienists)

TWA (Time-Weighted Average)

OSHA (Occupational Safety and Health Administration)

NIOSH (National Institute for Occupational Safety and Health)

Section 16: Other Information

ABBREVIATIONS USED IN THE SDS:


NDA: No Data Available

Hazardous Material Information System (HMIS)

HEALTH	1
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	H

HMIS & NFPA Hazard Rating Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



DISCLAIMER: The information contained herein is based on data available to us and is believed to be correct . WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 8/16/2016