



## 1. Product Name

LaqFlat-A

## 2. Manufacturer

WOOD KOTE PRODUCTS INC  
8000 NE 14<sup>th</sup> PI (97211)  
PO Box 17192  
Portland OR 97217  
Tel: (800) 843-7666 (USA & Canada)  
Tel: (503) 285-8371  
Fax: (503) 285-8374  
[info@woodkote.com](mailto:info@woodkote.com)  
[www.woodkote.com](http://www.woodkote.com)

## 3. Product Description

### BASIC USE

LaqFlat-A is intended for professional use only. It is a flattening agent additive formulated to reduce gloss levels in Wood Kote nitrocellulose-based lacquers. LaqFlat-A is an additive and not a coating, and thus it is not subject to the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99).

### ADVANTAGES

- Consistent formulation
- Convenient

### COMPOSITION & PROPERTIES

LaqFlat-A is made from flattening agents combined with solvents and resin to form an easily dispersible agent.

### TYPES

LaqFlat-A is available from the factory in one formulation.

### SIZES

LaqFlat-A is sold in 32-fl oz (946ml), 1-Gal (3,8L), 5-Gal (19L) and 55-Gal (208,5L) metal containers.

## 4. Technical Data

### PHYSICAL PROPERTIES

See table 1

## 5. Installation

LaqFlat-A is intended to be used as an additive only. It is recommended that a MiniTint or MacroTint be used for accurate measurement. LaqFlat-A should be thoroughly dispersed into lacquer using an air or spark-proof electric mixer or mechanical agitation for no less than 2 minutes.

### PRECAUTIONS

LaqFlat-A is flammable. Therefore, be certain that on-site conditions allow for adequate ventilation and pose no threat of fire or other health hazards. LaqFlat-A should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

### CLEAN UP

If spilled, clean surfaces using an absorbent cloth. MiniTint or MacroTint dispensing devices can be cleaned with LaqThin T-99A (lacquer thinner) AceThin (acetone). Any cloth containing LaqFlat-A, lacquer thinner or acetone should be left unfolded to dry in open air before disposal.

## 6. Availability & Cost

### AVAILABILITY

LaqFlat-A is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

### COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

## 7. Warranty

LaqFlat-A is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote



warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

## 8. Maintenance

### STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

### DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

## 9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.

## 10. Filing Systems

- Wood Kote-Product Catalog
- Additional product information is available from the manufacturer.
- [www.woodkote.com](http://www.woodkote.com)

Physical Properties Table 1

Mfr No	APPEARANCE	VOC gm/L	FLASH PT
604A	Translucent	Exempt (597)	11°F (-17,2°C)

LaqFlat-A



This page intentionally left blank.

A