



1. Product Name

PolyFlat 450

2. Manufacturer

WOOD KOTE PRODUCTS INC
8000 NE 14th PI (97211)
PO Box 17192
Portland OR 97217
Tel: (800) 843-7666 (USA & Canada)
Tel: (503) 285-8371
Fax: (503) 285-8374
info@woodkote.com
www.woodkote.com

3. Product Description

BASIC USE

PolyFlat 450 is intended for professional use only. It is a flattening agent additive formulated to reduce gloss levels in Wood Kote solvent-based polyurethanes. PolyFlat 450 is an additive and not a coating, and thus it is not subject to the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99).

ADVANTAGES

- Consistent formulation
- Convenient

COMPOSITION & PROPERTIES

PolyFlat 450 is made from flattening agents combined with solvents and resin to form an easily dispersible agent.

TYPES

PolyFlat 450 is available from the factory in one formulation.

SIZES

PolyFlat 450 is sold in 32-fl oz (946ml), 1-Gal (3,8L), 5-Gal (19L) and 55-Gal (208,5L) metal containers.

4. Technical Data

PHYSICAL PROPERTIES

See table 1

5. Installation

PolyFlat 450 is intended to be used as an additive only. It is recommended that a MiniTint or MacroTint be used for accurate measurement. PolyFlat 450 should be thoroughly dispersed into polyurethane using an electric mixer or mechanical agitation for no less than 2 minutes.

PRECAUTIONS

PolyFlat 450 should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

CLEAN UP

If spilled, clean surfaces using an absorbent cloth. Any cloth containing PolyFlat 450 should be left unfolded to dry in open air before disposal.

6. Availability & Cost

AVAILABILITY

PolyFlat 450 is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

7. Warranty

PolyFlat 450 is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or obtained by Wood Kote from sources believed by Wood



Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

8. Maintenance

STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.

10. Filing Systems

- Wood Kote—Product Catalog
- Additional product information is available from the manufacturer.
- www.woodkote.com

Physical Properties Table 1

Mfr No	APPEARANCE	VOC gm/L	FLASH PT
605A	White	Exempt (490)	105°F (40,5°C)

This page intentionally left blank.

