



1. Product Name

X-Link-R

2. Manufacturer

WOOD KOTE PRODUCTS INC
8000 NE 14th PI (97211)
PO Box 17192
Portland OR 97217
Tel: (800) 843-7666 (USA & Canada)
Tel: (503) 285-8371
Fax: (503) 285-8374
info@woodkote.com
www.woodkote.com

3. Product Description

BASIC USE

X-Link-R is intended for professional use only. It is an additive formulated to catalyze and promote cross-linking of Clear and Clean II. X-Link-R is an additive and not a coating, and thus it is not subject to the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99).

ADVANTAGES

- Consistent formulation
- Convenient
- Versatile

COMPOSITION & PROPERTIES

X-Link-R is made from diethylene glycol monoethyl ether acetate and polyfunctional aziridine.

TYPES

X-Link-R is available from the factory in one formulation.

SIZES

X-Link-R is sold in ½-fl oz (14,8ml) and 2- fl oz (59ml) quantities. Both

are sold in 2-fl oz (59ml) HDPE plastic containers.

4. Technical Data

PHYSICAL PROPERTIES

See table 1

5. Installation

X-Link-R is intended to be used as an additive only. It should be thoroughly dispersed into Clear and Clean II using an electric mixer or hand mixing stick for no less than 2 minutes. Under normal conditions, 2 fl oz/gal (15,5 ml/L) should be sufficient.

PRECAUTIONS

X-Link-R is poisonous and must be handled with extreme caution. Additional product may be required when additional working time is needed. DO NOT exceed 48 hours after first catalyzation or 8 fl oz/gal (62 ml/L). X-Link-R should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Safety Data Sheet (SDS).

CLEAN UP

If spilled, X-Link-R should be cleaned from surfaces using an absorbent cloth. Any cloth containing X-Link-R should be left unfolded to dry in open air before disposal.

6. Availability & Cost

AVAILABILITY

X-Link-R is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

7. Warranty

X-Link-R is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided



herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

8. Maintenance

STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.



10. Filing Systems

- Wood Kote–Product Catalog
- Additional product information is available from the manufacturer.
- www.woodkote.com

Physical Properties Table 1

Mfr No	APPEARANCE	VOC gm/L	FLASH PT
608	Clear	Exempt (519)	224.6°F (107°C)

This page intentionally left blank.

A