



Korrekt-O

1. Product Name

Korrekt-O

2. Manufacturer

WOOD KOTE PRODUCTS INC
8000 NE 14th PI (97211)
PO Box 17192
Portland OR 97217
Tel: (800) 843-7666 (USA & Canada)
Tel: (503) 285-8371
Fax: (503) 285-8374
info@woodkote.com
www.woodkote.com

3. Product Description

BASIC USE

Korrekt-O liquid colorants are intended for professional use only. They are formulated for tinting Wood Kote solvent-based pigment stains, glazes, lacquers and polyurethanes. Korrekt-O is an additive and not a coating, and thus it is not subject to the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99).

ADVANTAGES

- High color strength
- Uniform color
- Quick and easy dispersion
- Available in small (16 fl oz) dispensing containers

COMPOSITION & PROPERTIES

Korrekt-O liquid colorants are formulated with a variety of fine pigments, acrylic resin, propylene glycol monomethyl ether acetate (PMA) and naphthol spirits.

TYPES

Korrekt-O liquid colorants are available from the factory in 15 colors.

SIZES

Korrekt-O liquid colorants are sold in 16-fl oz (473ml) HDPE squeeze bottles with dispensing tips, 32-fl oz (946ml), 1-Gal (3,8L) and 5-Gal (19L) metal containers.

4. Technical Data

PHYSICAL PROPERTIES

See table 1

5. Installation

It is recommended that a MiniTint or MacroTint be used for accurate measurement of Korrekt-O liquid colorants. All containers of colorant should be agitated by hand or machine for no less than 30 seconds immediately prior to dispensing. Korrekt-O liquid colorants should be thoroughly dispersed into stains, lacquers and polyurethanes using an electric mixer or mechanical agitation for no less than 2 minutes.

PRECAUTIONS

Korrekt-O should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

CLEAN UP

Clean surfaces, MiniTint or MacroTint dispensing devices and metal tools using an absorbent cloth with LaqThin T-99A (lacquer thinner).

6. Availability & Cost

AVAILABILITY

Korrekt-O liquid colorants are available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

7. Warranty

Korrekt-O liquid colorants are sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

8. Maintenance

STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).



C

DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.

10. Filing Systems

- Wood Kote–Product Catalog
- Additional product information is available from the manufacturer.
- www.woodkote.com

C

Physical Properties Table 1

Mfr No	COLOR	VOC gm/l	FLASH POINT
0061	White	387	108°F (42,2°C)
0451	Scarlet	567	108°F (42,2°C)
1063	Red	550	116°F (46,7°C)
5558	Green	566	108°F (42,2°C)
7262	Blue	590	108°F (42,2°C)
8852	Violet	591	108°F (42,2°C)
9955	Black	538	108°F (42,2°C)
2555	Bright Yellow	461	108°F (42,2°C)
1863	Yellow	608	116°F (46,7°C)
0550	Bright Red	617	116°F (46,7°C)
1352	Burnt Umber	537	116°F (46,7°C)
2075	Raw Umber	550	116°F (46,7°C)
0982	Orange	575	108°F (42,2°C)
2852	Organic Yellow	545	116°F (46,7°C)
9451	Purple	580	108°F (42,2°C)