



## 1. Product Name

Jel'd Stain 550 Premium

## 2. Manufacturer

WOOD KOTE PRODUCTS INC  
8000 NE 14<sup>th</sup> PI (97211)  
PO Box 17192  
Portland OR 97217  
Tel: (800) 843-7666 (USA & Canada)  
Tel: (503) 285-8371  
Fax: (503) 285-8374  
[info@woodkote.com](mailto:info@woodkote.com)  
[www.woodkote.com](http://www.woodkote.com)

## 3. Product Description

### BASIC USE

Jel'd Stain 550 Premium is intended for professional use only. It is formulated for interior wood surfaces such as casework, doors, trim, paneling and cabinets. It is formulated with finely ground solvent-based liquid dispersion colorants to achieve custom colors with subtle depth and exceptional intensity. Jel'd Stain 550 Premium may be applied to bare or bleached wood. It is compatible with a variety of other Wood Kote products. Please refer to the *Wood Kote Schedule of Product Compatibility and Recommended Dry Times*. Jel'd Stain 550 Premium complies with the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99).

### ADVANTAGES

- Intense colors
- Subtle depth
- High Intensity
- 2-3 times more coverage than liquid stains
- Meets US VOC regulations

### COVERAGE

One application of Jel'd Stain 550 Premium will cover approximately 1250-1500 sq ft/gal (30,6-36,8 m<sup>2</sup>/L). Recoating is not recommended.

### COMPOSITION & PROPERTIES

Jel'd Stain 550 Premium is a semi-transparent pigment wood stain. It is intended for application without thinning. If thinning is desired, PolySolvent (mineral spirits) should be used or, if regulations require a VOC-exempt thinner, use AceThin (acetone).

### TYPES

Jel'd Stain 550 Premium is available from the factory in 7 colors. It can be tinted with Korrekt-O or Perfect-O colorants to achieve variations of the custom colors.

### SIZES

Jel'd Stain 550 Premium is sold in 12-fl oz (335ml), 32-fl oz (946ml), 1-Gal (3,8L), 5-Gal (19L) and 55-Gal (208,5L) metal containers.

## 4. Technical Data

### PHYSICAL PROPERTIES

See table 1

## 5. Installation

Complete installation specifications and recommendations are available from the manufacturer.

### PREPARATORY WORK

#### Applicator Qualifications

All work shall be performed by skilled tradesmen experienced in performing work of this type and under the direction of a capable foreman.

#### Samples

For each finish system indicated at least two 8-1/2"x11" (19x24,6 cm) pieces should be provided for approval. If it is apparent conditions may allow substantial variations, a sufficient number of samples should be created to indicate the parameters of the variations. Those samples marked "approved" by architect/specifier shall serve as the standard for similar work throughout the project.



### Inspection

Verify all surfaces to be finished will be maintained within a temperature range of 45-80°F (7-27°C) during application and curing period. Verify all surfaces to be finished are clean and dry. Use an electric moisture meter to test all wood surfaces. Do not proceed if reading is higher than 15% without written permission from architect/specifier.

### Surface Preparation

Sand all wood surfaces in the direction of the wood grain with the appropriate abrasive grit specified on the finish schedules (usually between 80-220 grit). Sand all wood surfaces until all machine marks and glue are removed and each species has achieved a uniform smoothness without rough or burnished areas. Remove all sanding dust from the surfaces to be finished and from the work area.

### APPLICATION

Jel'd Stain 550 Premium is formulated to be applied by hand in-shop or on-site with a soft clean lint-free cloth. Jel'd Stain 550 Premium should be rubbed into the grain of the wood with a circular motion and the excess wiped away in the direction of the wood grain. It should be applied in a manner that the application is uniform in color, must be free of streaks, blotches or other defects detrimental to appearance or performance.





**PRECAUTIONS**

For on-site application, be certain local applicable VOC regulations do not supercede Federal regulations. Be certain that on-site conditions allow for adequate ventilation and pose no threat of fire or other health hazards. Jel'd Stain 550 Premium is a wood stain and must be properly top-coated with lacquer or polyurethane to achieve a complete wood finish. Because Jel'd Stain 550 Premium has a high pigment content, certain topcoats can lift the color from the stain. Use extreme caution when applying a topcoat directly over Jel'd Stain 550 Premium with a brush or wipe-on tool. Jel'd Stain 550 Premium IS NOT recommended for application on floors. DO NOT mechanically agitate. This product has been tested on a very limited number of substrates (and coatings). In addition, a very limited number of coatings have been tested over this product. The applicator is responsible for testing suitability and performance for the specific application. In all cases, Wood Kote strongly recommends testing the

entire finish system on an equivalent substrate before applying to the project. Jel'd Stain 550 Premium should only be applied by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

**CLEAN UP**

Clean tools and surfaces with an absorbent cloth and PolySolvent.

**6. Availability & Cost**

**AVAILABILITY**

Jel'd Stain 550 Premium is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

**COST**

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

**7. Warranty**

Jel'd Stain 550 Premium is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or

obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

**8. Maintenance**

**STORAGE**

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

**CLEANING & REPAIR**

Jel'd Stain 550 Premium is intended to be top-coated, and therefore, cannot be directly cleaned or repaired. If repair or replacement is desired, the entire finish system must be removed and reapplied. Jel'd Stain 550 Premium should be removed from wood with a chemical stripper (paint and varnish remover) or by mechanical means (sanding).

**DISPOSAL**

Dispose of only in accordance with local, state and federal regulations.

**9. Technical Services**

Additional information is available directly from the manufacturer and from the manufacturer's web site.

**10. Filing Systems**

- Wood Kote–Product Catalog
- Additional product information is available from the manufacturer
- www.woodkote.com

Physical Properties Table 1

Mfr No	COLOR	VOC gm/L	FLASH PT
331	Blood Red	<550	104°F (40°C)
332	Orange	<550	104°F (40°C)
333	Yellow	<550	104°F (40°C)
334	Red	<550	104°F (40°C)
335	Indigo Blue	<550	104°F (40°C)
336	Forest Green	<550	104°F (40°C)
337	Burgundy	<550	104°F (40°C)