



1. Product Name

LaqThin

2. Manufacturer

WOOD KOTE PRODUCTS INC
8000 NE 14th PI (97211)
PO Box 17192
Portland OR 97217
Tel: (800) 843-7666 (USA & Canada)
Tel: (503) 285-8371
Fax: (503) 285-8374
info@woodkote.com
www.woodkote.com

3. Product Description

BASIC USE

LaqThin is intended for professional use only. It is an aggressive general-purpose solvent used to reduce the viscosity, control the flow, application and the final appearance of Wood Kote nitrocellulose-based lacquers. LaqThin T-4 is a high quality formulation recommended for fine finishes. LaqThin T-99A will dissolve dry lacquers and is recommended for general use and clean up of application tools.

ADVANTAGES

- Consistent formulation
- Economical
- Wide variety of uses

COMPOSITION & PROPERTIES

LaqThin is a blend of ketones, glycol ethers, and aliphatic solvents.

TYPES

LaqThin is available from the factory in 2 formulations. LaqThin T-99A and LaqThin T-4.

SIZES

LaqThin is sold in 1-Gal (3,8L), 5-Gal (19L) and 55-Gal (208,5L) metal containers.

4. Technical Data

PHYSICAL PROPERTIES

See table 1

5. Installation

LaqThin is intended to be used as a diluent only where regulations allow. Under normal conditions, the amount of LaqThin should not exceed 10% of the undiluted product.

PRECAUTIONS

LaqThin is extremely flammable. Therefore, be certain that on-site conditions allow for adequate ventilation and pose no threat of fire or other health hazards. It is intended to be used as an additive or cleaning solvent only where regulations allow. LaqThin should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

CLEAN UP

If spilled, clean surfaces using an absorbent cloth. Any cloth containing LaqThin should be left unfolded to dry in open air before disposal.

6. Availability & Cost

AVAILABILITY

LaqThin is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

7. Warranty

LaqThin is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's



knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

8. Maintenance

STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.

10. Filing Systems

- Wood Kote—Product Catalog
- Additional product information is available from the manufacturer.
- www.woodkote.com

LaqThin

SO

Physical Properties Table 1

Mfr No	PRODUCT	VOC gm/L	FLASH PT
4930A	LaqThin T-99A	804	1°F (-17,2°C)
4520	LaqThin T-4	827	20°F (-6,7°C)

This page intentionally left blank.

