



## 1. Product Name

Jel'd Lin Soap

## 2. Manufacturer

WOOD KOTE PRODUCTS INC  
8000 NE 14<sup>th</sup> PI (97211)  
PO Box 17192  
Portland OR 97217  
Tel: (800) 843-7666 (USA & Canada)  
Tel: (503) 285-8371  
Fax: (503) 285-8374  
[info@woodkote.com](mailto:info@woodkote.com)  
[www.woodkote.com](http://www.woodkote.com)

## 3. Product Description

### BASIC USE

Jel'd Lin Soap is intended for professional use only. It is a general-purpose gelatinous soap used to clean a variety of surfaces such as leather and stainless steel. It is specially formulated to be used as a lubricant where hydrocarbon-based products are unacceptable. It has good adhesion to a variety of surfaces and at room temperature is dissolution resistant to flowing water.

### ADVANTAGES

- Economical
- Stable gel
- Effective cleaner and lubricant

### COVERAGE

Depending on the application and porosity of the substrate, Jel'd Lin Soap will cover approximately 500-1,000 sq ft/gal (12.2-24.5m<sup>2</sup>/L).

### COMPOSITION & PROPERTIES

Jel'd Lin Soap is made from pure linseed oil. It is a medium-pH linseed oil soap manufactured using a traditional saponification process. Jel'd Lin Soap contains no chelating agents.

## TYPES

Jel'd Lin Soap is available from the factory in one formulation: Gelled.

## SIZES

Jel'd Lin Soap is sold in 32-fl oz (946ml), 1-Gal (3,8L) and 5-Gal (19L) plastic containers.

## Technical Data

### PHYSICAL PROPERTIES

See table 1

### Installation

Complete installation specifications and recommendations are available from the manufacturer.

### APPLICATION

Jel'd Lin Soap is intended for hand application in-shop or on-site. For cleaning, wear rubber gloves and apply with a soft clean lint-free cloth. Jel'd Lin Soap should be rubbed onto the surface with a circular motion. The excess should be wiped away with second damp clean lint-free cloth until the surface is streak free. If the situation allows, the surface can be rinsed with flowing water. An alternative cleaning method is to mix Jel'd Lin Soap and hot water in a plastic bucket. Start with a mild solution of Jel'd Lin Soap in water (approximately 1 part Jel'd Lin Soap to 8 parts water). Begin cleaning an area approximately 10 sq ft (1 m<sup>2</sup>) with a sponge, cloth or soft scrub brush and the Jel'd Lin Soap solution. Remove the dirty solution from the area with a sponge. If you are not satisfied with the cleaning power of the solution you may add more Jel'd Lin Soap until the cleaning properties are satisfactory. Repeat the cleaning process until the entire area is clean and excess solution has been removed. For lubrication purposes, such as tire slip or boring cores, Jel'd Lin Soap should be applied generously directly from the container to the pertinent surfaces using rubber gloves and protective clothing.



### PRECAUTIONS

**IMPORTANT:** Jel'd Lin Soap can discolor some surfaces. It is recommended that compatibility be tested in an inconspicuous area before use. Jel'd Lin Soap should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

### CLEAN UP

If spilled, clean up using an absorbent cloth or sponge.

## 6. Availability & Cost

### AVAILABILITY

Jel'd Lin Soap is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

### COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

## 7. Warranty

Jel'd Lin Soap is sold without warranty except that Wood Kote guarantees that the product is manufactured within the





specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

**11. Maintenance**

**STORAGE**

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

**CLEANING & REPAIR**

Jel'd Lin Soap is a maintenance product, and therefore, cannot be directly cleaned or repaired. It can be re-applied as often as required.

**SHELF LIFE**

Jel'd Lin Soap should retain its effectiveness for at least 5 years under recommended storage conditions.

**DISPOSAL**

Dispose of only in accordance with local, state and federal regulations.

**12. Technical Services**

Additional information is available directly from the manufacturer and from the manufacturer's web site.

**13. Filing Systems**

- Wood Kote–Product Catalog
- Additional product information is available from the manufacturer
- [www.woodkote.com](http://www.woodkote.com)



Physical Properties Table 1

Mfr No	COLOR	% WT SOLIDS	VOC gm/L	FLASH PT
S7032-S7640	Dark Amber	39.5	0	N/A